

Rogue™ R2 Wash



Rogue™ R2 Wash makes a valuable addition to rental and production inventories. Durable and dependable, this moving wash workhorse produces a bright, powerful light and offers four zones of LED control via its 19 (15 W) RGBW LEDs. An industry leading zoom range of 12-49° gives the Rogue™ R2 Wash the spread to cover even the largest areas. Smooth color mixing and six distinct dimming modes, simple and complex DMX channel profiles and powerCON® in and out are just some of the other features that make this fixture a standout performer in any setting.

FEATURES

- 19 RGBW LEDs, 15 W each
- 5 zones of LED control for pixel mapping control
- Unique lens design for excellent color blending
- Fast, smooth pan and tilt movement
- 6 distinct dimming modes for advanced control
- 3- and 5-pin DMX input/output connections
- Omega mounting bracket, fits all Rogue™, Next™, and Legend™ fixtures
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility

SPECIFICATIONS

- DMX Channels: 15, 17, 22, 33, 54 or 56
- Data Connectors: 3- and 5-pin XLR
- Light Source: 19 LEDs (quad-color RGBW)
15 W, (1 A), 50,000 hours life expectancy
- Pan and Tilt: 540°/230°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/
90°, 180°, 230° tilt
- Automatic Pan/Tilt Correction: Yes
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 8° to 30°
- Field Angle: 12° to 49°
- Zoom Angle: 12° to 49°
- Dimming Modes: 6
- Illuminance (12°): 8,650 lux @ 5 m
- Illuminance (49°): 750 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 4 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 339 W, 2.95 A @ 120 V, 60 Hz
- Power and Current: 324 W, 1.62 A @ 208 V, 60 Hz
- Power and Current: 324 W, 1.50 A @ 230 V, 50 Hz
- Weight: 20.4 lb (9.25 kg)
- Dimensions: 8.58 x 12.05 x 15.67 in (218 x 306 x 398 mm)
- Approvals: CE, MET